


Features

- ✓ Heat sink design better for air convection, good heat dissipation.
- ✓ CREE COB LED, up to 80 lm/W, CRI 80+.
- ✓ Dimming capability. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification.


Specifications

Model	MD02-09	
Voltage	AC200-240V 50/60Hz	
Power	9W	
LED	CREE COB LED	
Luminous Flux	2700K	609lm
	3000K	703lm
	4000K	709lm
	5000K	747lm
Efficiency	80 lm/W	
CRI	80+	
Beam Angle	Reflector 15°/28°/40°/60°	
Dimmable	Yes, leading edge, trailing edge and universal	
IP Rated	IP40	
Lifespan	> 40,000Hrs	
Dimension	Ø49.8*H68mm	
Packaging	L130*W80*H110mm	
Carton	L54*W41.5*H35CM, 60pcs/CTN	
Warranty	3 years	






Technical Data Test

40D



Light Source Test Report



DOWNLIGHT LED MODULE Features: Heat sink design better for air convection, good heat dissipation. CREE COB LED, 9W, up to 80 lm/W, CRI 80+. Dimming capability. Suits triac dimmers including Shuttle LED dimmer, OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification